



INKJET080 CLEAR GLOSS

Clear glossy easily removable printfilm.

Face material

Gloss clear soft vinyl.

Type Soft vinyl

Colour and Finish Gloss clear

Weight 104 g/m² ±10% ISO-536

Thickness 80 µ ±10% ISO 534-80

Adhesive

Acrylic removable adhesive featuring good clarity and clean removability from glass, laminated plastics and crosslinked enamels. Not suitable for application on papers, PVC and air dried paints and varnishes.

Reference: AR801

Type: Acrylic removable

Min. Appl. Temp.: +5°C

Service Temp.: -40°C/+120°C

Shear: High

Tack: 2 N/25mm FINAT FTM9

Final Adhesion: 2 N/25mm FINAT FTM2

This adhesive complies with FDA 175.105

Liner

Type: One side siliconised clay coated Kraft

Colour and Finish: White

Weight: 135 g/m² ±10% PP-032 - ISO 536

Thickness: 145 µ ±10% ISO 534

Transparency: n.a. % DIN 53 147-64

Application

Promotional labels, big size window stickers and electro welded pouches.

Printing methods



Printable with solvent based and UV screenprinting, offset UV. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

Shelf life is 2 years, when stored at 23 °C and 50 % relative humidity conditions. Higher temperatures and/or humidity levels will reduce product shelf life. **Storage conditions:**

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources

Disclaimer

All Carl Jensen's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Carl Jensen's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Carl Jensen's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Carl Jensen's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Carl Jensen material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Carl Jensen's products are used in conditions beyond its control, such as those listed above as example, Carl Jensen does not assume any liability for inappropriate use of the products.

Carl Jensen reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Carl Jensen's products are sold subject to Carl Jensen's general terms and conditions of sale listed in the following Carl Jensen's web page: www.carl-jensen.com