



## SUPER CANVAS 400 GR/M2 - PVC FREE

100% cotton PVC Free fabric













### Advantages

- canvas like fabric
- 100 % cotton
- trimming cold (no fraying)

### Application

- frame tensioning systems
- art reproduction

### Technical data

Substrate		DIN 60001	100 % cotton
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	400 g/m <sup>2</sup>
Fire retardancy		DIN 4102 B1, M1, NFPA 701, CA 1237	yes
Application			indoor
Width		DIN EN ISO 2286-1	max. 220 cm / 87 inch (see overview)
Print side			outside
Roll length			25 ± 0,5 m
Type of ink		  	all kinds of solvent inks, UV-curable inks, latex inks

### Printing Methods

All kinds of solvent inks, UV-curable inks, latex inks Testing for suitability between media, printers and inks is always recommended prior to use.



## Other things



The material might, depending on humidity and temperature, shrink until 2-3 %. The shrink has to be checked before printing.

## Disclaimer

All Carl Jensen's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Carl Jensen's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Carl Jensen's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Carl Jensen's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Carl Jensen material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Carl Jensen's products are used in conditions beyond its control, such as those listed above as example, Carl Jensen does not assume any liability for inappropriate use of the products.

Carl Jensen reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Carl Jensen's products are sold subject to Carl Jensen's general terms and conditions of sale listed in the following Carl Jensen's web page: [www.carl-jensen.com](http://www.carl-jensen.com)