

Technical Data Sheet

Issue date: 13/05/2011 Date last modification: 13/12/2016

INDUSTRIAL - AUTOMOTIVE

4-IL2E-06934 STONE GUARD PU 150 ASP8A PERMANENT PET75

Face Material

Gloss clear Pu film.

PU film Type Colour and Finish Gloss clear

ISO-536 Weight 202 g/m² ±10% ISO 534-80 Thickness 150 µ ±10%

Adhesive

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

ASP8A permanent Reference Type Acrylic permanent

+10°C Min. Appl. Temp. Service Temp. -40 / +140 Shear Very high High N/inch2 Tack Final Adhesion Very high N/inch

Liner

One side siliconised Pet Type

Colour and Finish Clear

PP-032 - ISO Weight 105 g/m²

536 ±10%

Thickness 75 u ±10% ISO 534 DIN 53 147-64 Transparency n.a. %

Applications

Specially designed for various automotive surfaces, this material provides protection against paintwork chips and abrasion caused by stones etc.

Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of $22^{\circ}C \pm 2^{\circ}C$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



