



## URBANTEX UPCYCLING FR - 100% PVC FREE

### Advantages

- Matt surface
- Canvas like fabric
- Made of 100 % PET bottle recycled yarn
- Trimming cold (no fraying).

### Applications

- Banner
- Frame tensioning systems
- Art reproduction
- Wall covering\*\*

### Face Material

A white print media with a white backside made of min. 80 % recycled polyester, B1 approved. Cut without heat.

Type	min. 80 % recycled polyester	
Colour and Finish	White	
Weight	220 g/m2	DIN EN ISO 2286-2
Weave	Woven fabric	DIN ISO 9354
Substrate	Min. 80% recycled polyester	DIN 60001
Fire retardancy	Yes	DIN 4102 B1
Application	Indoor	
Width	Up to 1.620mm	DIN EN ISO 2286-1
Roll length	30 meters	
Surface	Satin – semi mat	

### Printing Methods

Urbantex Upcycling are printable with all kinds of solvent inks, UV-curable inks\*, latex inks.



### Disclaimer

All Carl Jensen's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Carl Jensen's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Carl Jensen's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.



The methods of conversion and application of Carl Jensen's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Carl Jensen material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.

As Carl Jensen's products are used in conditions beyond its control, such as those listed above as example, Carl Jensen does not assume any liability for inappropriate use of the products.

Carl Jensen reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Carl Jensen's products are sold subject to Carl Jensen's general terms and conditions of sale listed in the following Carl Jensen's web page: [www.carl-jensen.com](http://www.carl-jensen.com)

\* please consider the risk of curling because UV-curable inks will still be hardening after a while

\*\* please test in advance; the adhesive behavior depends on the surface applied